CE

ŞİŞECAM

Declaration of Performance
No: CRZ0600NL

TRC ECOTHERM 6 mm

2007

Trakya Cam Sanayii A.Ş.
İş Kuleleri Kule 3 34330
4.Levent- İSTANBUL/TÜRKİYE
Tel: +90 212 350 50 50
www.trakyacam.com.tr/en/ce

EN 1096-4:2006
Notified Test Body: 1750

Off-Line Coated Glass Heat Control Glass (Low-E, on single plate) , intended to be used in buildings and construction works

Characteristics	AVCP System	Performance
Safety in the case of fire:		
Resistance to fire (13501-2)	1	NPD
Reaction to fire (13501-1)	3,4	A1
External fire behaviour (EN 13501-5)	3,4	NPD
Safety in use:		
Bullet resistance (EN 1063)	1	NPD
Explosion resistance (EN 13541)	1	NPD
Burglar resistance (EN 356)	3	NPD
Pendulum body impact resistance (EN 12600)	3	NPD
Resistance against sudden temperature changes and temperature differentials	4	NPD
Wind, snow, permanent and imposed load resistance of the glass unit	4	6mm
Protection aganist noise:		
Direct airborne sound reduction (EN 12758)	4	31 (-2; -3) dB
Thermal properties:		
U-value (EN 673)	3	NPD
Normal emissivity (EN 12898)	3	0.04
Radiation properties (EN 410):		
Light transmission	3	0.87
Light reflection indoor (coated side)	3	0.04
Light reflection outdoor (uncoated side)	3	0.06
Solar energy characteristics (EN 410):		
Solar transmission	3	0.58
Solar reflection indoor (coated side)	3	0.28
Solar reflection outdoor (uncoated side)	3	0.19

NPD: No performance determined

The performance of the product identified is in conformity with the declared performance above.
This declaration of performance is issued under the sole responsibility of the manufacturer.
Signed for and on behalf of the manufacturer by:

Name and function	Place and date of issue	Signature
Gökhan Atikkan Basic Glass Production Director	01 July 2013 İstanbul	